

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8158-9)  
-----  
Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on W side for the ¼ sec. cor., from which  
    A fir, 10" dia., bears N.84°E., 14 lks., mkd: ¼ S BT.  
    A laurel, 10" dia., bears N.71°W., 32 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-50  
-----  
Found - No trace of 10" Laurel as it lies in clear cut unit. 10", now 11" D.Fir N.84°E., 9.2 ft., faint bark scribe "BT", other marks but not legible.  
Set - Brass Cap at Cor. mkd: County Surveyors T31S R8W Office, 1967 S 18|S 17  
New BTs- 14" D.Fir N.51°E. 20.0 ft. mkd. ¼ S17 CS BT.  
          7" D.Fir N.68°W. 20.5 ft. mkd. ¼ S18 CS BT.  
Note - This corner lies about 460 ft. south & 250 ft. E. of creek. To determine if 11" D.Fir was old enough, I notch to count rings which were almost too close together to count. Definitely old enough.

Fd. BC and 3 BTs by C. Woodruff, 4/2008 - M156-5

Ron Quimby - Crew: N. Fromdahl, J Leonard & R. Olsen - 2/2015 - C.S. File 65/87-17  
-----  
Found - DCSO brass cap  
          12" 4' high fir stump (rotted) vis scribe N.51°E., 20.0 ft.  
          18" D.Fir N.68°W., 20.5 ft. good scribe.  
New - 6" fir S.16°E., 22.6' scribed ¼ S17 BT.  
      7" Fir S.37°W., 26.0' scribed ¼ S18 BT.  
      Compass decl. 15½°E.