

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8161)

-----  
Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked 1/4 S for the 1/4 sec. cor., from which

A fir, 40" dia., bears S.60°E., 12 lks., mkd: 1/4 S BT.

A cedar, 12" dia., bears N.65°W., 21 lks., mkd: 1/4 S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13213)

-----  
The 1/4 sec. cor. of secs. 7 & 8, determined at record bearing and distance from the remains of the original bearing trees:

A rotted fir stump, 40" dia., bears S.60°E., 12 lks., to face, no marks remaining.

A cedar, 17" dia., bears N.65°W., 21 lks., mkd. 1/4 S on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd.

	1/4	
S 7		S 8
T31S		R8W
		1962

from which new BTs

A fir, 13" dia., bears S.65°E., 42 lks., mkd: 1/4 S8 BT.

A fir, 30" dia., bears N.48°W., 34 lks., mkd: 1/4 S7 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C Stone - January 1967 - C.S. File 54/36-44

-----  
Found - GLO Brass Cap at 1/4 Corner, properly marked in 1962. Orig. Cedar NOW 19" N.67°W. 14.1 ft., scribe visible but faint 1/4 S.

1962 - 34" D.Fir N.48°W., 22.4 ft. Tree has about half of top broken out, scribe visible "1/4 S7 BT".

12 D.Fir, S.65°W. 27.7 ft., shows pitched over scribing, not legible.

New BT - 31" D.Fir S.59°W., 26.2 ft., mkd. 1/4 S 7 CS BT.

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group No. 819, surveyed Aug./Sept. 1972 - (DCSO Records Vol. 36 Page(s) 14934)

-----  
The 1/4 sec. cor. of secs. 7 & 8, monumented with an iron post, 2 1/2" dia., firmly set, protruding 6" above ground with brass cap (properly) marked. continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remaining original bearing tree  
A cedar, 18" dia., bears S.65°E., 21 lks., with scribe  
marks ¼ S visible on opened blaze.  
and bearing trees marked by White, Corbin, and Beck  
A fir, 14" dia., bears S.65°E., 42 lks., with healed  
blaze.  
A fir, 32" dia., bears N.48°W., 34 lks., with scribe marks  
¼ S7 BT visible on partially healed blaze.  
and a BT mkd by Powell, in 1967  
A fir, 32" dia., bears S.60½°W., 39 lks., with scribe  
marks ¼ visible on partially healed blaze.