

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; and 5, T32-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8101)

-----  
Set stone 14x12x10 ins., 8" in the ground, mkd. ¼ on N. side for the ¼ sec. cor., and from which

A Fir 52" dia., bears N.9°E., 52 lks. dist. mkd. ¼ S BT.

A Fir 40" dia., bears S.32°W., 75 lks. dist. mkd. ¼ S BT

Milner L. Larson - July 1956 - C.S. File 42/167and M 3-3

-----  
Found 2 original BTs.

Set 1/2" Iron pipe for corner point.

Scribed 1 new BT:

14" Madrone, N.15°00'W., 8.1 ft.

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 1967 - C.S. File 54/36-76

-----  
Found - 5/8" Iron rod (not 1/2" I.P.) at ¼ corner.

No trace of original stone.

Orig. 52" D.Fir now down, N.9°E., 34.3 ft.

Orig. 40" now 54" D.Fir S.32°W., 49.5 ft., old axe work visible, snag top.

Call of 33.0 ft. from creek hits very good.

Renewal BT:

14" Laurel N.15°W., 8.1 ft., scribe visible "3642BT"

New BT - 20" D.Fir S.9°W., 23.5 ft. mkd. ¼ S5 CS BT.

Corner lies West of creek 33.0 ft.

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #2004, survey March/Oct. 2002- (DCSO records Vol. 54 Page(s) 21082-3)

-----  
The ¼ sec. cor. of secs. 5 & 32, perpetuated & recorded by Larson, in 1956, subsequently perpetuated & recorded by the Douglas County Surveyors Office in 1967; monumented with an iron rod, 5/8" dia., firmly set, projecting 8" above the ground, in a collar of stone, 1 ft. base, to top, from which the remains of the original bearing trees

A uprooted fir, 52" dia., bears N.9°E., 34.3 ft., no face visible.

A fir snag, 60" dia., bears S.32°W., 49.5 ft., with illegible scribe marks visible on partially healed blaze.

and a bearing tree mkd. by Larson

A madrone, 20" dia., bears N.15°W., 8.1 ft., with healed double blaze.

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; and 5, T32-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and a bearing tree mkd. by the Douglas County Surveyor  
A fir, 29" dia., bears S.9°W., 23.5 ft., with healed blaze  
At the corner point

Set a stainless steel post, 28" long, 2½" dia., directly over  
the iron rod, 26" in the ground, in a collar of stone, with  
brass cap mkd.

T 31 S R 8 W  
¼  $\frac{S\ 32}{S\ 5}$

T 32 S  
2002

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.