

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8157)

-----

Set a fir post 3 ft. long, 3" sq., 18" in the ground marked 1/4 S on N side for the 1/4 sec. cor., from which

A fir, 48" dia., bears N.20°E., 24 lks., mkd: 1/4 S BT.

A fir, 20" dia., bears S.72°E., 122 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group No. 819, surveyed Aug./Sept. 1972 - (DCSO Records Vol. 36 Page(s) 14931-2)

-----

Point for the 1/4 sec. cor. of secs. 17 & 20, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 22" in the ground with brass cap marked:

T31S R8W  
1/4     S 17  
          S 20  
          1973

from which

A fir, 20" dia., bears N.58°W., 80 lks., mkd: 1/4 S17 BT.

A fir, 20" dia., bears S.74°E., 10 lks., mkd: 1/4 S20 BT.