

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8160)

Set a chittenwood post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on N side for the ¼ sec. cor., from which
A fir, 36" dia., bears N.32°E., 47 lks., mkd: ¼ S BT.
A fir, 48" dia., bears South, 22 lks., mkd: ¼ S BT.

Reported as not fd, 1/1967 - DCSO, JMP - C.S. File 54/36-63

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group No. 819, surveyed Aug./Sept. 1972 - (DCSO Records Vol. 36 Page(s) 14933)

Point for the ¼ sec. cor. of secs. 8 & 17, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked:

T31S R8W
¼ $\frac{S \ 8}{S \ 17}$
1973

from which

A fir, 12" dia., bears N.59°E., 55 lks., mkd: ¼ S8 BT.
A fir, 25" dia., bears S.39°E., 54 lks., mkd: ¼ S17 BT.