

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8140)  
-----  
Set a fir post 3 ft. long, 3" sq. 18" in the ground marked ¼ S on W side, for the ¼ sec. cor., from which  
    A cedar, 15" dia., bears N.35°E., 10 lks., mkd: ¼ S BT.  
    A fir, 15" dia., bears S.50°W., 49 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey - S.A. Bilow - Aug. 1958 - C.S. File 49/109-7  
-----  
Found - Both Orig. BTs.  
    Orig. 15", now 30" R.Fir S.50°W. 32.3 ft. Shows good scar above & good bark scribe at base "BT".  
    Orig. 15", now 30" cedar N.35°E. 6.6 ft., shows good scars above & below. I do not. open.  
Set Brass Cap at Corner Mkd: County Surveyors Office, 1958  
    ¼ S32 S33, T31S R8W.  
    I rescribe 30" cedar N.25°E. 7.0 ft. ¼ S33 CS BT.  
    I rescribe 30" R.Fir S.47°W. 29.1 ft. ¼ S32 CS BT.  
Note - Byars apparently used slope distances to BTs. Byars measured to face of BT, we measure to center.

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #2004, survey March/Oct. 2002- (DCSO records Vol. 54 Page(s) 21086)  
-----  
The ¼ sec. cor. of secs. 32 & 33, perpetuated and recorded by the Douglas County Surveyors Office in 1958, and recorded in C.S. file No. 49/109; monumented with an iron post, 1" dia., firmly set, projecting 18" above the ground, in a collar of stone, 2 ft. base to top, with brass cap (properly) mkd. from which the original bearing trees  
    A cedar, 40" dia., bears N.25°E., 6.6 ft., with healed blaze. (Record, N.35°E.)  
    A fir, 38" dia., bears S.47°W., 29.1 ft., with healed blaze. (Record, S.50°W., 32.3 ft.)