

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor Secs 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8141)

Set a stone 20x16x12", 10" in the ground, marked with 4 notches on the E & 1 notch on the S angles of same, for the cor. to secs. 28, 29, 32 & 33, and from which
A fir, 10" dia., bears N.50°E., 15 lks., mkd: T31S R8W S28 BT.
A fir, 26" dia., bears S.45°E., 45 lks., mkd: T31S R8W S33 BT.
A laurel, 10" dia., bears S.30°W., 24 lks., mkd: T31S R8W S32 BT.
A laurel, 8" dia., bears N.45°W., 60 lks., mkd: T31S R8W S29 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey - S.A. Bilow - Aug. 1958 - C.S. File 49/109-6

Found - 18x10x14" Stone at Corner & 3 Orig. BTs
Orig. 10", now 14" Fir N.50°E. 9.9 ft., shows old scar. I do not open.
Orig. 26", now 30" Fir S.45°E. 29.1 ft., shows faint but definite bark scribe "BT 33".
Clump of Laurels that checks bearing & distance for SW BT.
Orig. 8", now 15" Laurel N.45°W. 39.6 ft., shows good scar. I do not open.
Set Brass Cap at Corner & Alongside Corner Stone, Marked
Brass Cap: S29|S28 T31S R8W COUNTY SURVEYORS OFFICE 1958
S32|S33
New BTs- Rescribe 14" R.Fir N.32°E. 10.7 ft S28 T31S R8W CSBT
Rescribe 15" Laurel N.45°W. 36.7 ft S29 T31S R8W CSBT
(Bark)Rescribe 30" R.Fir S.43°E. 30.2 ft. S33 T31S R8W CS BT.
Bark Scribe 32" R.Fir S.83°W. 28.6 ft. S32 T31S R8W CS BT.