

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8142)

Set a stone 18x12x8", 8" in the ground, marked $\frac{1}{4}$ on the W side for the $\frac{1}{4}$ sec. cor. from which

A fir, 13" dia., bears S.80°E., 44 lks., mkd: $\frac{1}{4}$ S BT.

A fir, 16" dia., bears S.75°W., 13 lks., mkd: $\frac{1}{4}$ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Cliff Stone - Jan. 1967 - C.S. File 54/36-61

Found - No trace of stone at corner.

13" Fir, now stump, S.80°E., 29.0 ft. bark scribed " $\frac{1}{4}$ S" visible.

16" Fir, now stump, S.75°W., 8.6 ft., nothing visible on this tree (find bearing to be N.82°W.)

Post at corner. using 2 distances & 1 bearing, I renew.

Set - Brass cap at $\frac{1}{4}$ cor. mkd: COUNTY SURVEYORS T31S R8W OFFICE, 1967 $\frac{1}{4}$ S29|S28

New BTs- 14" Chinquapin S.8°W., 56.6 ft. mkd. $\frac{1}{4}$ S29 CS BT.

18" Cedar S.59 $\frac{1}{2}$ °E., 112.2 ft. mkd. $\frac{1}{4}$ S28 CS BT.

Note - This corner lies about 40 ft. north of skid road & 130.0 ft. south of draw.