

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8142)

Set a stone 15x14x10", marked with 4 notches on the E & 2 notches on the S edge, 8" in the ground for the cor. to secs. 20, 21, 28, & 29, from which
 A Live Oak, 4" dia., bears N.64°E., 9 lks., mkd: T31S R8W S21 BT.
 A Laurel, 6" dia., bears S.12°E., 17 lks., mkd: T31S R8W S28 BT.
 A Fir, 14" dia., bears S.15°W., 15 lks., mkd: T31S R8W S29 BT.
 A Laurel, 5" dia., bears N.30°W., 19 lks., mkd: T31S R8W S20 BT.

Milner L. Larson - July 1956 - C.S. file 42/168 & M3-4

No trace of the original corner could be found.
Corner reestablished by proportionate measurement.
Set a 1½" iron pipe, from which:
 5" Madrone, N.15°15'E., 24.9 ft.
 5" Madrone, S.69°00'E., 8.9 ft.
 30" Fir, S.12°10'W., 24.1 ft.
 6" Madrone, N.40°00'W., 6.5 ft.

Fd. Ok by Steven Ness, Dec. 1981 - M89-65
Fd. Ok by Les Roberts, April 1995 - 1995-0046