

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8144)

Marked a fir 7" in dia., T31S T8W S16 on NE face, S 21 on SE face, S20 on SW face and S17 on NW face. Also 3 notches on the S & 4 notches on the E angles of same, for the cor. to Secs. 16, 17, 20, & 21, from which
A fir, 16" dia. bears N.80°E., 10 lks mkd: T31S R8W S16 BT
A fir, 10" dia. bears S.20°E., 24 lks mkd: T31S R8W S21 BT
A fir, 7" dia., bears S.85°W., 5 lks. mkd: T31S R8W S20 BT
A fir, 8" dia. bears N.12°W., 27 lks. mkd: T31S R8W S17 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey - S.A. Bilow - Aug. 1958 - C.S. File 49/109-1

Found - Orig. 16", now 16" Fir Snag N.80°E. 6.6 ft. Shows faint scribing "16 BT 8"
Orig. 10", now 26" fir previously opened, shows good scribing "BT". Record bearing S.20°E., distance checks O.K. 15.8 ft.
No trace of Corner Tree nor BT to SW Or BT to NW
Set Brass Cap at Corner Mkd: S17|S16T31S R8W County Surveyors S20|S21 Office, 1958
New BTs- 34" R.Fir bears N.32½°W. 10.9 ft. scribed S17 T31S R8W CS BT
16" R.Fir bears S.53°W. 33.0 ft. scribed S20 T31S R8W CS BT.
6" R.Fir N.35°E., 56.6 ft. scribed S16 CS BT.
The Orig. SE BT is Ok I do not rescribe, bearing is S.11°E.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Cliff Stone - Jan. 1967 - C.S. File 54/36-62

Found - 1958 County Surveyors BC at Corner, properly mkd
Orig. 10", now 22 Fir, S.11°E., 15.8 ft., shows good scar.
34" R.Fir N.32½°W., 10.9 ft. mkd. T31S R8W S17 CS BT
16" R.Fir, broken & dead, S.53°W., 33.0 ft. mkd. T31S R8W S20 CS BT.
6" R.Fir N.35°E., 56.6 ft. mkd. T31S R8W S16 CS BT.
New BT - 22" D.Fir S.44°W. 36.7 ft. mkd. T31S R8W S20 CS BT.
Note - This corner lies 155.0 ft. W of Dutchman Lookout RD

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13204)

The cor. of secs. 16,17, 20, & 21, perpetuated by & recorded in the County Surveyors Office, in 1958, nonumented with an iron pipe, 1½" dia., 12" above ground, firmly set, at record distance from the remaining original bearing trees, with brass cap (properly) mkd.

from which original bearing trees:

A fir snag, 14" dia., bears N.80°E., 10 lks., with illegible scribe marks visible on open blaze,

A fir, 27" dia., bears S.15°E.; 24 lks., with scribe marks BT visible on opened blaze. (Record bearing, S.20°E.) and bearing trees mkd. in 1958.

A fir, 15" dia., bears S.53½°W., 50 lks., mkd. T31S R8W S20 CS BT on open blaze.

A fir, 32" dia., bears N.33½°W., 18 lks., mkd. T31S R8W on partially healed blaze, and a new bearing tree

A fir, 24" dia., bears N.83½°E., 55 lks., mkd. T31S R8W S16 BT.

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group No. 819, surveyed Aug./Sept. 1972 - (DCSO Records Vol. 36 Page(s) 14930-1)

The cor. of secs. 16, 17, 20, & 21, perpetuated and recorded by Byron, in 1958, monumented with an iron post, 1" dia., firmly set, protruding 12" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir snag, 14" dia., bears N.80°E., 10 lks., with fragmentary scribe marks visible on opened blaze.

A fir, 27" dia., bears S.15°E., 24 lks., with scribe marks BT visible on opened blaze. and bearing trees marked by Byron

A fir, 15" dia., bears S.53½°W., 50 lks., with scribe marks T31S R8W S20 CS BT visible on open blaze.

A fir, 32" dia., bears N.33½°W., 18 lks., with scribe marks T31S R8W visible on partially healed blaze. and a bearing tree marked by White, Corbin, and Beck

A fir, 24" dia., bears N.83½°E., 55 lks. with healed blaze
From Plat:

Latitude: 42°52.2'N Longitude: 123°39.5'W

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20, & 21

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Fd. Ok by Steven Ness, Dec. 1981 - M89-65
Fd. Ok by Les Roberts, April 1995 - 1995-0046

Mark Smalley - For: Roseburg Forest Products - 10/14/2003 -
C.S. File 65/48-40

Found - 1958 DCS0 IPBC
32" Fir S.11°E., 15.8 ft. Good OBT
40" Fir N.32½°W., 10.9 ft. good
18" Fir S.53°W., 33.0 ft. cut down
6" Fir N.35°E., 56.6 ft. good
26" Fir S.44°W., 36.7 ft. good - 1967
New - 21" Fir S.18°W., 22.5 ft. scribed "S 20 BT"
Dec. 19°