

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8146)

Set a fir post 4 ft. long, 4" sq., 20" in the ground, marked T31S R8W S9 on the NE, S16 on SE, S17 on the SW, & S8 on the NW faces. Also 4 notches on the East & South angles of same, for the cor. to secs. 8, 9, 16, & 17, from which

A fir, 18" dia. bears N.60°E., 69 lks. mkd: T31S R8W S9 BT
A fir, 8" dia. bears S.30°E., 62 lks. mkd: T31S R8W S16 BT
A fir, 36" dia. bears S.60°W. 41 lks. mkd: T31S R8W S17 BT
A fir, 48" dia. bears N.50°W., 25 lks. mkd: T31S R8W S8 BT

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13205)

The cor. of secs. 8, 9, 16, & 17, determined at record bearing and distance from the remaining original BTs:

A fir, 13" dia., bears S.30°E., 62 lks., with scribe marks S16 visible on partially opened blaze.
A fir snag, 48" dia., bears N.50°W., 25 lks., with a healed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, and in a mound of stone, 2½ ft. base to top, with brass cap mkd.

T31S	R8W
<u>S 8</u>	<u>S 9</u>
S 17	S 16
1960	

from which new bearing trees

A fir, 28" dia. bears N.10°E., 50 lks. mkd. T31S R8W S9 BT
A fir, 13" dia. bears S.40°E. 36 lks. mkd. T31S R8W S16 BT
A fir, 6" dia. bears S.40¼°W. 76 lks. mkd. T31S R8W S17 BT
A fir, 8" dia. bears N.14½°W., 55 lks. mkd. T31S R8W S8 BT

Mark Smalley - For: Roseburg Forest Products - Dec. 13, 1996 - C.S. 65/13-9I

Found - 1960 BLM Cad. IPBC
29" Fir snag, N.10°E., 50 lks. poor healed face
10" Fir snag, N.14½°W., 55 lks. dead
17" W.Fir, S.40¼°W., 76 lks. good healed face

New BTs- 7" Fir, N.30°E., 23.8' scribed "S 9 BT"
10" Fir, S.69°E., 47.2, scribed "S 16 BT"

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group No. 819, surveyed Aug./Sept. 1972 - (DCSO Records Vol. 36 Page(s) 14932-3)

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2½" in dia., firmly set, protruding 10", above ground, and in a mound of stone, 2½ ft. base, to top, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir, 15" dia., bears S.30°E., 62 lks., with scribe marks S16 visible on partially healed blaze.

A fir snag, 48" dia., bears N.50°W., 25 lks., with healed blaze.

and bearing trees marked by White, Corbin, and Beck

A fir, 28" dia., bears N.10°E., 50 lks. with healed blaze.

A fir, 16" dia., bears S.40°E., 36 lks. with healed blaze.

A fir, 6" dia., bears S.40¼°W., 76 lks. with healed blaze.

A fir, 12" dia. bears N.14½°W., 55 lks. with healed blaze.