

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8147)

-----  
Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked 1/4 S on the W face, for the 1/4 sec. cor., from which  
A fir, 36" dia., bears S.10°E., 5 lks., mkd: 1/4 S BT.  
A fir, 18" dia., bears S.40°W., 4 lks., mkd: 1/4 S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13206)

-----  
The 1/4 Sec. cor. of secs. 8 & 9, determined at record bearing and distance from the original bearing trees:

A fir, 40" dia., bears S.10°E., 5 lks., with scribe marks 1/4 S BT visible on bark blaze.  
A fir, 22" dia., bears S.40°W., 4 lks., with scribe marks 1/4 BT visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in mound of stone, 2 ft. base, to top, with brass cap mkd.

1/4  
S 8 | S 9  
T31S | R8W  
1961

from which new bearing trees

A fir, 30" dia., bears N.45°E., 23 lks., mkd: 1/4 S9 BT.  
A fir, 12" dia., bears N.86 3/4°W., 48 lks., mkd: 1/4 S8 BT.