

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4, T32-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8100)

Set a Fir post 3 ft. long, 3" sq., 20" in the ground mkd. ¼ S for the ¼ sec. cor., from which

A Laurel 14" dia., bears N.65°E., 23 lks. dist. mkd. ¼ S BT.

A Laurel 14" dia., bears S.15°W., 25 lks. mkd. ¼ S BT.

Lorne Swearingen - For: The Robert Dollar Co. - Dec. 29, 1959 - C.S. File 51/63-1 - Witnessed by Robert Harris & Milner Larson.

Found to be in poor condition. The original BTs are still here but the scribing has nearly all rotted away. Since the orig. BTs are Madrona, I scribed two new BTs and marked the corner as follows:

The corner was mkd. with a 1¼" (O.D.) iron pipe driven 18" into the ground, from which

A 12" D.Fir S.39½°E., 45.3 ft., was referenced and scribed S4 ¼S 4186 BT.

A 9" P.Pine N.22°E., 52.3 ft. was referenced and scribed S33 ¼S 4186 BT.

BTs were referenced with a compass & chain.

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 1967 - C.S. File 54/36-72

Found - Orig. 14" now 17" Laurel, N.65°E., 15.2 ft., opened for scribing, rotten.

Orig. 14" now 18" Laurel, S.15°W., 16.5 ft., opened for scribing "T".

13" Fir, now down, S.39½°E., 45.3 ft., scribed, pitched over.

Also Iron pipe at ¼ cor.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 8 W

¼ $\frac{S \ 33}{S \ 4}$

T 32 S

1967

Reblazed and rescribed:

38" double Laurel S.15°W., 16.5 ft. mkd. ¼ S4 CSBT

New BT - 15" Laurel N.68°E., 22.8 ft. mkd. ¼ S33 CS BT.

As in original notes, corner lies about 33.0 ft. West of ridge top.

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4, T32-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ronald Quimby - For: Roseburg Resources Co. - March 2002 - M
139-64 A & B

Found - County Surveyor's Office brass cap, properly marked.
38" Madrone S.15°W, 16.5 ft. (Good scar)
18" Madrone N.68°E, 22.8 ft. (Good scar)
18" Madrone N.65°E, 15.2 ft. (Rotted face)
New BTs- 7" Fir N.3°W, 14.6 ft. (Scribed 1/4 S33 BT)
8" Fir S.64°W 13.6 ft. (Scribed 1/4 S4 BT)