

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8145)

-----

Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked  $\frac{1}{4}$  S on the N side, for the  $\frac{1}{4}$  sec. cor., from which  
A fir, 12" dia., bears S.2°W., 48 lks., mkd:  $\frac{1}{4}$  S BT.  
A laurel, 12" dia., bears N.20°W., 17 lks., mkd:  $\frac{1}{4}$  S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13203)

-----

The  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, determined at record bearing and distance from the remaining original BT:  
A down fir, 25" dia., bears S.2°W., 48 lks., with illegible scribe marks visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, with brass cap marked:

$\frac{1}{4}$   $\frac{S\ 16}{S\ 21}$   
T31S R8W  
1961

from which

A fir, 42" dia., bears N.69 $\frac{1}{2}$ °E., 38 lks., mkd.  $\frac{1}{4}$  S16 BT.  
A fir, 13" dia., bears S.45°E., 84 lks., mkd.  $\frac{1}{4}$  S21 BT.