

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8146-7)

Marked a permanent stone $\frac{1}{4}$ S on N side, stone 18" above ground 12x10" for the $\frac{1}{4}$ sec. cor., from which
A fir, 14" dia., bears N.22°E., 30 lks., mkd: $\frac{1}{4}$ S BT.
A fir, 16" dia., bears South, 55 lks., mkd: $\frac{1}{4}$ S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13204-5)

Point for the $\frac{1}{4}$ sec. cor. of secs. 9 & 16, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 $\frac{1}{2}$ " dia., 22" in the ground with brass cap marked:

$\frac{1}{4}$ $\frac{S \ 9}{S \ 16}$
T31S R8W
1961

from which
A fir, 18" dia., bears N.62°W., 18 lks., mkd: $\frac{1}{4}$ S9 BT.
A cedar, 5" dia., bears S.13°E., 22 lks., mkd: $\frac{1}{4}$ S16 BT.