

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8130-1)

-----  
Set a stone 12x10x8", 8" in the ground, marked ¼ on W side for the ¼ sec. cor. from which

A fir, 24" dia., bears S.70°E., 19 lks., mkd: ¼ S BT.

A fir, 16" dia., bears West, 28 lks., mkd: ¼ S BT

-----  
Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-52

-----  
Found - 24" D.Fir, now down, S.70°E. 12.5 ft., faint bark scribe "BT", other marks visible but not legible.  
16" D.Fir, now down, west 18.5 ft. This tree previously opened but lying on face.

Set - Brass Cap at Cor. mkd: County Surveyors T31S R8W Office, 1967 ¼ S 33|S34

New BTs- 24" Fir S.1½°W. 129.8 ft. mkd. ¼ S33 CS BT.

46" Fir N.47°E. 52.0 ft. mkd. ¼ S34 CS BT.

Note - This cor, lies about 200 ft. S. & 60 ft. W. of ridge top.