TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8132)

Set a stone 14x12x8" in the ground, marked ¼ on W side for the ¼ sec. cor. from which
A cedar, 6" dia., bears N.70°E., 14 lks., mkd: ¼ S BT.
A laurel, 14" dia., bears West, 4 lks., mkd: ¼ S BT

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16205)

The ¼ sec. cor. of secs. 27 & 28, monumented with the original basalt stone, 14x12x8", loosely set, 4" in the ground, mkd. ¼ on W. face, from which an original BT:
A cedar, 24" dia., bears N.70°E., 14 lks., with scribe marks BT visible on partially open blaze.
At the corner point
Set an iron post. 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T31S R8W

¼
S 28 | S 27
1976

from which a new BT
A cedar, 23" dia., bears N.86¾°W., 46½ lks. mkd: ¼ S28 BT.
Deposit corner stone alongside iron post.

Mark Smalley, L.S. 2354 - 12/10/93 - C.S. File 63/154-3

Found - 1977 Cad. BCIP
24" Cedar, N.70°E., 9.2'. fair condition.
23" Cedar, N.86¾°W., 30.7', tall stump.
New BTs- 20" Fir, S.77°E., 35.0', scribed "¼ S27 BT".
16" Madrone, N.64°E., 20.9', scribed "¼ S27 BT".
17" Fir, N.9°E., 24.4', scribed "¼ S27 BT".