

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8132-3)

Set a stone 12x10x10", 8" in the ground, marked with 3 notches on the East & 2 notches on the South angles of the same, for the corner to Secs. 21, 22, 27 & 28, from which

A Live Oak, 4" dia., bears N.37°E., 20 lks., mkd: T31S R8W S22 BT.

A Fir, 22" dia. bears S.5°E., 46 lks. mkd: T31S R8W S27 BT

A Fir, 15" dia. bears S.8°W., 57 lks. mkd: T31S R8W S28 BT

A Fir, 28" dia. bears N.25°W., 9 lks. mkd: T31S R8W S21 BT

Douglas Co. Surveyors Office - John M. Powell & Crew - 3/24/1970 - C.S. File 54/36-33

Found - No trace of corner stone.

Orig. 22" now 36" D.Fir S.5°E., 30.4 ft., no scribe visible.

Orig. 15" now 20" D.Fir S.8°W., 37.6 ft., no scribe visible, other faint mks.

Orig. 4" Live Oak, now stob, N.37°E., 13.2 ft.

Orig. 28", now 45" D.Fir N.67°W., 5.9 ft. (Rec. N.25°W. 5.9) no scribe found.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R8W
OFFICE S 21 | S 22
1970 S 28 | S 27

New BTs- 10" D.Fir N.66°E., 16.5 ft. mkd: T31S R8W S22 CS BT

10" D.Fir N.26°W., 34.8 ft. mkd: T31S R8W S21 CS BT

Reblazed & rescribed -

36" D.Fir S.5°E., 30.4 ft. mkd: T31S R8W S27 CS BT

20" D.Fir S.8°W., 37.6 ft. mkd: T31S R8W S28 CS BT

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16205-6)

The cor. of secs. 21, 22, 27, and 28, perpetuated and recorded by Byron, in 1910, monumented with an iron post. 1½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which the remaining orig. BTs

A fir, 36" dia., bears S.8½°E., 48 lks., with healed blaze. (Record, S.5°E., 46 lks.)

A fir, 23" dia., bears S.8°W., 57 lks., with healed blaze.

A fir, 42" dia., bears N.25°W., 7 lks., with healed blaze. (Record, 9 lks.)

and bearing trees mkd. by Byron

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 12" dia., bears N.65°E., 24½ lks., with healed blaze.
A fir, 11" dia., bears N.28°W., 52½ lks., with healed blaze.