

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8134)

Set a stone 20x10x8", 8" in the ground, mkd ¼ on W side for the ¼ sec. cor., from which
 A Live Oak, 8" dia., bears S.10°E., 15 lks., mkd: ¼ S BT.
 A Live Oak, 7" dia., bears N.40°W., 13 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - L.E. Monrean - M. Tompkins - Oct. 19, 1976 - C.S. File 59/24-37

Found stone laying on surface with an apparent "4/1" marked on top, found no other marks on stone. Stone measured 21x12x8" (Rec. 20x10x8") called to the South recorded as 72.6 ft. to creek. The distance from stone to creek measures approximately 121 ft. No scribing found on possible BTs. Did not set cap. Reported as not found.

Howard Johnstone - For: Roseburg Lbr. Co. - Nov. 22, 1977 - M65-49

Set - 5/8"x42" I.R. & alum cap with orig. stone marked ¼
 From orig. 8" Oak BT.
BTs - 8" Oak S.10°E., 9.9 ft. Orig.
 7" Oak N.40°W., 8.6 ft. Orig. (down)
 10" Oak N.84°E., 17.6
 30" Madrone N.26°W., 16.0