

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8134)

-----  
Set a stone 16x12x6", 8" in the ground, marked with 3 notches on the East & South angles of the same, for the corner to secs. 15, 16, 21, & 22, and from

A cedar, 10" dia., bears N.45°E., 29 lks., mkd: T31S R8W S15 BT.

A fir, 14" dia. bears S.85°E. 36 lks. mkd: T31S R8W S22 BT

A fir, 24" dia. bears S.85°W. 35 lks. mkd: T31S R8W S21 BT

A fir, 8" dia. bears N.70°W., 62 lks. mkd: T31S R8W S16 BT

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13198)

-----  
The cor. of secs. 15, 16, 21, and 22, determined at record bearing and distance from the remaining original BTs:

A cedar, 16" dia., bears N.45°E., 29 lks., with old axe marks visible on bark.

A fir, 26" dia., bears S.85°E., 36 lks., with scribe marks T31S R W B visible on bark.

A fir, 36" dia., bears S.85°W., 35 lks., with scribe marks 8 W BT visible on bark.

At the corner point

Set an iron post, 28" long, 2¼" dia., 24" in the ground, with brass cap mkd.

T31S R8W

S 16 | S 15

S 21 | S 22

1961

from which new BTs

A fir, 25" dia., bears N.56°E., 66 lks., mkd: T31S R8W S15 BT.

A fir, 30" dia., bears N.58°W., 110 lks., mkd: T31S R8W S16 BT.