

TOWNSHIP 31 RANGE 8 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8136)

Set a live oak post 4 ft. long, 4" sq., 20" in the ground, marked T31S R8W S10 on the NE, S15 on the SE, S16 on the SW and S9 on the NW faces. Also 3 notches on the East & r notches on the South angles of the same, for the cor. to secs. 9, 10, 15, & 16 from which

- A Laurel, 8" dia., bears N.1°E., 28 lks., mkd: T31S R8W S10 BT.
- A Laurel, 10" dia., bears S.45°E., 17 lks., mkd: T31S R8W S15 BT.
- A Laurel, 9" dia., bears S.25°W., 22 lks., mkd: T31S R8W S16 BT.
- A Fir, 20" dia. bears N.80°W., 26 lks. mkd: T31S R8W S9 BT

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13199)

The cor, of sees. 9, 10, 15, and 16, determined at record bearing & distance from the remaining original bearing tree:

- A fir, 32" dia., bears N.80°W., 26 lks., mkd. T31S R8W S9 BT on bark blaze. Remarkd T31S R8W S9 BT.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T31S	R8W
<u>S 9</u>	<u>S 10</u>
S 16	S 15
1961	

from which new BTs

- A fir, 25" dia. bears N.13°E. 55 lks. mkd: T31S R8W S10 BT
- A fir, 13" dia. bears S.86°E. 80 lks. mkd: T31S R8W S15 BT
- A fir, 23" dia. bears S.8°W., 37 lks. mkd: T31S R8W S16 BT

Dependent resurvey by Peter A. Peterson & Harvey E. Wofford, Cadastral Surveyors, under Group No. 446, surveyed Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14537)

The cor. of secs. 9, 10, 15, & 16, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap marked and witnessed as described in the official record of the 1961-64 dependent resurvey.

Fd Ok by Troy Rambo, 6/2005 - M148-7