

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8137-8)

Set a fir post 4 ft long, 4" sq., 20" in the ground, mkd T31S R8W S3 on NE, S10 on SE, S9 on SW & S4 on NW faces Also 5 notches on the S & 3 notches on the E angles of same, and from which

A fir, 10" dia. bears N.66°E., 25 lks. mkd: T31S R8W S3 BT
A fir, 24" dia. bears S.75°E., 8 lks. mkd: T31S R8W S10 BT
A fir, 10" dia. bears S.52°W., 27 lks. mkd: T31S R8W S9 BT
A fir, 10" dia. bears N.25°W., 14 lks. mkd: T31S R8W S4 BT

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13201)

The cor. of secs. 3, 4, 9, & 10, determined at record distance from the remaining original bearing trees:

A fir, 28" dia., bears S.75°E., 8 lks., mkd. T R8W S10 BT on bark blaze.
A fir, 14" dia., bears S.68°W., 27 lks., mkd. with rotted face. (Record bearing, S.52°W.)
A fir, 16" dia., bears N.66°W., 14 lks. mkd. with healed blaze. (Record bearing, N.25°W.)

At the corner point
Set an iron post, 28", long, 2½" dia., 22" in the ground, with brass cap mkd.

T31S	R8W
<u>S 4</u>	<u>S 3</u>
S 9	S 10
1961	

from which new bearing trees

A fir, 6" dia., bears N.65°E., 41 lks. mkd. T31S R8W S3 BT
A fir, 17" dia. bears S.56½°W. 44 lks. mkd. T31S R8W S9 BT
A hemlock, 6" dia., bears N.27½°W., 65 lks., mkd. T31S R8W S4 BT.

Troy Rambo - For: Seneca Jones Timber Co. - 7/2005 - M148-7

Found - 1961 BLM brass cap
Rec. 28" Fir - in good condition.
Rec. 14" Fir - rotten snag
Rec. 16" Fir - now a low stump - no marks
Rec. 7" Hemlock - gone
Rec. 7" Fir (now 19") - in good condition.

New - Scribed "S10 BT" on an 18" GF - bears S.3°E. 18.0 ft
Scribed "BT" on 7" DF - bears S.79°W., 23.0 ft
Also chopped an "X" 4 ft. above stump height.