

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8139)

Set a yew post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on the W side for the ¼ sec. cor., from which
 A fir, 26" dia., bears N.42°E., 22 lks., mkd: ¼ S BT.
 A fir, 12" dia., bears N.30°W., 21 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - 12/30/1966 - C.S. File 54/36-60

Found - Orig. 26" Fir, now stump, N.42°E., 14.5 ft., shows scar.
 Orig. 12", now 19" W.Fir N.30°W. 13.9 ft., found scribing on rotten face.
Set - Brass Cap at ¼ Cor. mkd: County Surveyors T31S R8W Office, 1966 ¼ S4|S 3
New BTs- 5" D.Fir N.19°E. 18.8 ft. mkd. ¼ S 3 CS BT.
 38" D.Fir N.23°W. 24.0 ft. mkd. ¼ S 4 CS BT.
Note - This corner lies south of creek about 90.0 ft.

Gerald Nygren - For: Seneca Jones Timber - 4/2015 - M169-26

Found - 1966 CS Brass cap
 1882: 19" W.Fir, now snag, bears N.30°W., 13.9'
 1966: 5" W.Fir, now 12" stump, bears N.19°E., 18.8'
 1966: 38" D.Fir, now stump, bears N.23°W., 24.0'
New - 5" D.Fir bears S.20°W., 13.0' scribed: "X BT"
 14" D.Fir bears N.40°E., 58.9' scribed: "¼ S3 BT"