TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8131-2)

Set a laurel post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on the N side for the ¼ sec. cor., from which
A laurel, 10" dia., bears N.32°W., 19 lks., mkd: ¼ S BT.
A laurel, 12" dia., bears S.40°W., 48 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 6/17/1969 - C.S. File 54/36-38

Reported as not found
Old ribbon line toward this ¼ cor. from sec. cor. This also not fd. last year.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16203-4)

Point for the ¼ sec. cor. of secs. 27 & 34, at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T31S R8W

¼ S 27 / S 34

1977

from which
A madrone, 9" dia., bears N.6¼°W., 3 lks., mkd: ¼ S27 BT.
A fir, 5" dia., bears S.5½°W., 23 lks., mkd: ¼ S34 BT.