

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8135)

-----  
Set a Laurel post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on N side for ¼ Sec. Cor., from which  
A fir, 22" dia., bears N.10°E., 16 lks., mkd: ¼ S BT.  
A fir, 40" dia., bears South, 60 lks., mkd: ¼ S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13197)

-----  
The ¼ sec. cor. of secs. 15 and 22, determined at record bearing and distance from the remaining original BT:

A fir snag, 44" dia., bears South, 60 lks., mkd. S on bark blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap mkd.

¼  $\frac{S\ 15}{S\ 22}$   
T31S R8W  
1961

from which new BTs

A fir, 28" dia., bears N.44°E., 11 lks., mkd: ¼ S15 BT.

A fir, 41" dia., bears S.46½°E., 117 lks., mkd: ¼ S22 BT.