

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8136-7)

-----

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on N side for the ¼ sec. cor. from which

A fir, 18" dia., bears S.20°E., 27 lks., mkd: ¼ S BT.

A fir, 24" dia., bears N.10°W., 9 lks., mkd: ¼ S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13200)

-----

Point for the ¼ sec. cor. of secs. 10 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked:

¼  $\frac{S\ 10}{S\ 15}$

T31S R8W

1961

from which

A hemlock, 8" dia., bears N.16°W., 44 lks., mkd: ¼ S10 BT.

A fir, 9" dia., bears S.24°W., 59 lks., mkd: ¼ S15 BT.

Douglas Co. Surveyors Office - John M. Powell & Crew - 5/22/1972 - C.S. File 54/36-34

-----

Found - Gov't. Brass Cap under large 30" D.Fir Log.

8" Hemlock, now down, N.16°W. 29.0 ft scribe visible

9" W.Fir, now dead, S.24°W. 38.9 ft., scribe partly visible.

New BTs- 16" Cedar S.69°W. 77.8 ft. scribed "¼ S15 CS BT."

13" Hemlock N.38°W. 52.7 ft. scribed "¼ S10 CS BT".

Note - This corner lies on steep N. slope, also in old logged unit.