

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8138)

Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on N side for the ¼ sec. cor., from which
A fir, 18" dia., bears N.57°E., 46 lks., mkd: ¼ S BT.
A fir, 7" dia., bears S.45°W., 32 lks., mkd: ¼ S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13202)

The ¼ sec. cor. of secs 3 & 10, determined from the orig BTs:
A fir, 33" dia., bears N.55°E., 47 lks., with no marks remaining. (Record, N.57°E., 46 lks.) Remarked ¼ S3 BT.
A fir, 14" dia., bears S.42½°W., 33 lks., with axe marks on opened blaze. (Record, S.45°W., 32 lks.)
At the corner point
Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap mkd.
T31S R8W
¼ $\frac{S \quad 3}{S \quad 10}$
1961
from which a new bearing tree
A hemlock, 12" dia., bears S.73½°W., 49 lks. mkd. ¼ S10 BT