

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8121)

Set maple post 3 ft. long, 3" sq., 18" in the ground, marked 1/4 S on the W side, from which

A fir, 30" dia., bears S.68°E., 50 lks., mkd: 1/4 S BT.

A fir, 20" dia., bears N.24°W., 41 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16196-7)

Point for the 1/4 sec. cor. of secs. 34 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 24" in the ground with brass cap marked:

T31S R8W

1/4

S 34 | S 35

1977

from which

A fir, 8" dia., bears N.29°E., 20 lks., mkd: 1/4 S35 BT.

A fir, 12" dia., bears N.71°W., 23 1/2 lks., mkd: 1/4 S34 BT.