TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Secs. 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8123)

Set a laurel post 3" sq., 3 ft. long, 18" in the ground, marked ¼ S on the W side for the ¼ sec. cor. from which
A laurel, 4" dia., bears N.85°E., 17 lks., mkd: ¼ S BT.
A laurel, 5" dia., bears N.80°W., 16 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 6/1969 - C.S. File 54/36

6/17/1969 C.S. File 54/36-38
Not found. All that is here a a 4" & 5" laurel.
6/30/1969 - C.S. File 54/36-25
Not found. No good line. Ran line from approx cor. of 26, 27, 34, & 35 also not fd but was chained in by Tom Mhel (Dollar Lumber) BTs 2 laurels.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16198-9)

Point for the ¼ sec. cor. of secs. 26 & 27, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

T31S R8W
¼
S 27 | S 26
1977

from which
A fir, 9" dia., bears N.74½°E., 63 lks., mkd: ¼ S26 BT.
A fir, 5" dia., bears West, 43 lks., mkd: ¼ S27 BT

Tony Hostetter - For: Roseburg Resources Co. - July 2000 - C.S. File 65/33-6

Found - 1977 BLM brass cap & all BTs as described in 1977 dependent resurvey
New BTs- 14" Madrone, faced & scribed "S26 ¼ BT", BT tag, bears N.14°E., 6.0 ft. to 6" spike placed in root collar.
18" Tan Oak, faced & scribed "S26 ¼ BT", BT tag, bears N.35°30'E., 40.4 ft. to 6" spike placed in root collar.