

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8123)

-----  
Set a Stone 16x14x12" 8" in the ground, marked with 2 notches on the S & E angles of same for the cor. to Secs. 22, 23, 26 & 27, from which

- A Fir, 14" dia. bears N.70°E., 44 lks. mkd T31S R8W S23 BT
- A Fir, 12" dia. bears S.55°E., 26 lks. mkd T31S R8W S26 BT
- A Fir, 14" dia. bears S.35°W. 65 lks. mkd T31S R8W S27 BT
- A Fir, 15" dia. bears N.10°W., 16 lks. mkd T31S R8W S22 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - C.S. File 54/36-39

-----  
Found - Corner Stone, firmly in place, with 2 notches on E. Orig. 15, now 24" D.Fir, N.10°W., 10.6 ft., scribe visible.

- Orig. 14', now 22" D.Fir, S.32°W. 42.9 ft. (Rec. S.35°W.), tree burnt, no scribe.
- Orig. 12", now 19" D.Fir, S.55°E. 15.3 ft. (Rec. 17.2), scribe visible.
- Orig. 14", now 17" D.Fir, N.68E. 21.4 ft. (Rec. N.70°E. 17.2) scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyors T31S R8W  
(Set Alongside Corner Office S 22 | S 23  
Stone) 1970 S 27 | S 26

Reblazed. & Rescribed -  
24" D.Fir N.10°W. 10.6 ft. mkd: "T31S R8W S22 CS BT"  
22" D.Fir S.32°W. 42,9 ft. mid: "T31S R8W S27 CS BT"  
19" D.Fir S.55°E. 15.3 ft. mkd, "T31S R8W S26 CS BT"  
17" D.Fir N.68°E. 21.4 ft. mid: "T315 R8W S23 CS BT"

BLM Dependent resurvey by James E. Jelley, James J. Carlson, Cadastral Surveyors under Group #899 surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16199)

-----  
The cor. of secs. 22, 23, 26, & 27, perpetuated & recorded by Byron in 1970, monumented with an iron post, 1" dia. firmly set, projecting 8" above ground, with brass cap (properly) mkd., from which the remains of the original bearing trees

- A fir snag, 18" dia., bears N.64°E., 32 lks. with healed blaze. (Record, N.70°E., 44 lks.)
- A fir, 19" dia., bears S.55°E., 22½ lks. with fragmentary scribe marks visible on bark blaze. (Record, 26 lks.)
- A fir, 17" dia., bears S.30½°W., 65 lks. with fragmentary scribe marks vis on partially open blaze. (Rec S.35°W.)
- A fir, 29" dia., bears N.16°W., 18 lks. with healed blaze. (Record, N.10°W., 16 lks.)

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree  
A fir, 29" dia. bears N.55°E. 46 lks. mkd. T31S R8W S23 BT

Greg Lang - Aug. 18, 2004 - C.S. File 65/52-6  
-----

Found - Corner stone with Douglas County Brass cap set  
alongside. (Brass cap bears N.76¼°E., 0.50' from  
corner stone.)

A 22" Fir bears S.31°W., 42.24 ft (original)

A 30" Fir bears N.54¾°E., 30.17 ft (1977 BLM)

A 20" Fir bears S.53¼°E., 14.52 ft (original)

A 28" Fir bears N.6¾°W., 11.95 ft (original)

A Fir snag bears N.65¼°E., 21.50 ft (original)

Note - (We set spikes in the base of the existing bearing  
trees for measuring the distances to the corner;  
bearings to the trees were measured with a total  
station & are based on the 1977 resurvey of the  
north line of Section 26)

Corner lies the northerly side of a ridge and on a  
NE'ly slope.