

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8124)

Marked a permanent rock 24x16x16" above ground, for ¼ sec. cor. mkd. ¼ on N face, from which

- A fir, 24" dia., bears N.42°E., 40 lks., mkd: ¼ S BT.
- A fir, 36" dia., bears N.40°W., 45 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - L.E. Monrean - P. L. Earle - 12/24/1975 - C.S. File 57/39-47

Found - A Rock 2'x1.5'x1.5' above ground ¼ on northerly face
 Stone is firmly in place and lies in Darby Creek.
 A fir 24 (now 37) inch dia. bears N.42°E., 26.4 ft.
 Tree is bark scribed "¼ S BT"
 A fir 36 (now 51) inch dia. bears N.36°W., 28.3 ft. (rec. N.40°W., 29.7 ft.) Tree is bark scribed "¼ S BT T"
 Renewal- Chiseled "X" on flat surface of rock bears S.43°E., 30.9 ft. "X" is approx. 2¼" high. Flat surface on large boulder faces WNW and measures approx. 9" high by 32" long, and is approx. 14 ft. east of center of Darby CK.
 A D.Fir 6" dia. bears S.58°W., 51.9 ft. Tree Double blazed and scribed "¼ S22 CS BT" Mag. Dec. 20° E.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16201)

The ¼ sec. cor. of secs. 22 & 23, perpetuated and recorded by Francis L. Ingram, Co. Surveyor in 1975, monumented with the orig. basalt stone, in place, 24x16x16" above ground, mkd. ¼ on W face, from which the orig. BTs.

- A fir, 40" dia., bears N.42°E., 40 lks., with fragmentary scribe marks visible on bark blaze.
- A fir, 52" dia., bears N.40°W., 43 lks., with fragmentary scribe marks visible on bark blaze. (Rec. 45 lks.)

and a bearing object & BT mkd. by Ingram

- A basalt boulder, 3x2x1 ft. above ground, bears S.43°E., 47 lks. with X visible on NW face.
- A fir, 8" dia., bears S.58°W., 78½ lks. with healed blaze.

At the corner point
 Seat a brass tablet, 3¼" dia., 3½" stem, in drill hole, in top of corner stone, with top mkd: T31S R8W

¼
 S 22|S 23
 1977