

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor Secs 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8124-5)

Set a stone 15x12x10" mkd with 3 notches on the S & 2 notches on the E angles of same, for the corner to Secs. 14, 15, 22, & 23, from which
A Fir, 16" dia. bears N.25°E. 10 lks. mkd: T31S R8W S14 BT
A Fir, 8" dia., bears S.60°E., 9 lks. mkd: T31S R8W S23 BT
A Fir, 18" dia. bears S.7°W., 21 lks. mkd: T31S R8W S22 BT
A Fir, 12" dia. bears N.25°W. 57 lks. mkd: T31S R8W S15 BT

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13193-4)

The cor. of secs. 14, 15, 22, & 23, monumented with a stone, 15x12x10", firmly set, mkd. with 3 notches on the S & 2 notches on the E edges, from which the remaining orig. BTs:
A fir, 30" dia., bears N.25°E., 10 lks., mkd. T31S R8W S14 BT on bark blaze.
A down fir, 10" dia., bears S.60°E., 9 lks., with a healed blaze.
A fir, 18" dia., bears N.25°W., 57 lks., mkd. T31S R8 S15 BT on bark blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, and in mound of stone, 3 ft. base, to top, with brass cap mkd.
T31S R8W Lat: 42°52.0'N
S 15 | S 24 Long: 123°37.2'W
S 22 | S 23
1961
from which new BTs
A fir, 22" dia. bears N.61°E. 30 lks. mkd: T31S R8W S14 BT
A cedar, 10" dia., bears S.30°E., 57 lks., mkd: T31S R8W S23 BT.
A fir, 12" dia. bears S.50°W. 10 lks. mkd: T31S R8W S22 BT
A cedar, 6" dia., bears N.79°W., 45 lks., mkd: T31S R8W S15 BT.
Deposit orig. corner stone alongside iron post.

Claude Kerr, Reg. Eng. #2125 - July 31, 1951 (added 8/5/2024) - C.S. File 40/344-2

Fd rock, NE BT & NW BT in good condition, SE BT now a snag and SW BT gone.
Cruiser mark "K" was left on a BT to make it easier to find.
cont.

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor Secs 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16202)

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A fir, 33" dia., bears N.25°E., 10 lks., with scribe marks T31S R8W S14 BT visible on bark blaze.

A fir stump, 8" dia., bears S.55°E., 9 lks., with a down fir alongside, with fragmentary scribe marks visible on open blaze. (Record, S.60°E.)

A fir, 17" dia., bears N.25°W., 57 lks., with scribe marks T31S R8W S15 BT visible on bark blaze. and the remains of BTs mkd. by White, Corbin, & Beck in 1961

A fir, 20" dia., bears N.61°E., 30 lks., with healed blaze.

A cedar snag, 9" dia., bears S.30°E., 57 lks., with fragmentary scribe marks visible on open blaze.

A fir, 11 ins. diam., bears S.50°W., 10 lks., with healed blaze.

and a new BT

A fir, 30" dia., bears S.62¾°E., 56½ lks., mkd: T31S R8W S23 BT.