

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8126)

Set a cedar post 4" sq., 4 ft. long, 20" in the ground, mkd T31S R8W S11 on NE, S14 on SE, S15 on the SW, & S10 on the NW face. Also 4 notches on the S & 2 notches on the E angles of the same for the cor. to secs. 10, 11, 14, & 15, and from which:

- A fir, 40" dia. bears N.50°E. 38 lks. mkd: T31S R8W S11 BT
- A fir, 36" dia. bears S.65°E. 23 lks. mkd: T31S R8W S14 BT
- A fir, 48" dia. bears S.10°W. 34 lks. mkd: T31S R8W S15 BT
- A cedar, 10" dia., bears N.72°W., 32 lks., mkd: T31S R8W S10 BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13194-5)

The cor. of secs. 10, 11, 14, & 15, determined at record distance from the orig. BTs:

- A fir snag, 35" dia., bears N.45°E., 38 lks., mkd. S, B and other illegible scribe marks on bark blaze. (Record bearing, N.50°E.)
- A fir snag, 38" dia., bears S.74°E., 23 lks., mkd. T31 R8 S1 on old bark blaze. (Record bearing, S.65°E.)
- A fir snag, 55" dia., bears S.10°W., 34 lks., with no marks visible.
- A cedar, 25" dia., bears N.75°W., 32 lks., with a healed blaze. (Rec. bearing, N.72°W.) Remarked T31S R8W S10 BT

At the corner point

Set an iron post, 28" long, 2½" dia., 25" in the ground, & in a mound of stone, 2½ ft. base, to top, with brass cap marked:

T31S R8W
S 10 | S 11
S 15 | S 14
1961

from which

- A fir, 10" dia. bears N.24°E. 23 lks. mkd: T31S R8W S11 BT
- A fir, 7" dia. bears S.36°E., 28 lks. mkd: T31S R8W S14 BT
- A fir, 8" dia. bears S.34°W., 34 lks. mkd: T31S R8W S15 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-48

Found - GLO brass cap at sec. cor., properly mkd. in 1961.
11" W.Fir S.35°W., 21.5 ft., shows good scar. Not-
S.34°W., 22.4' continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

8" W.Fir S.35°E., 16.2 ft., scribe visible, "T31S R8W". Not - S.36°W., 18.5'

12" W.Fir N.20½°E., 15.6 ft., scribe visible "T31S R8W S11 BT". Not - N.24°E., 15.2'

Orig. 10" cedar, now down, N.72°W., 21.1 ft., good scar.

New BT - 28" Hemlock N.58°W., 40.0 ft mkd: T31S R8W S10 CS BT