

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8127)

-----  
Set a Fir post 3 ft. long, 3" sq. 18" in the ground for ¼ sec. cor. mkd: ¼ S on the W face from which  
A W.Fir, 20" dia., bears East, 8 lks., mkd: ¼ S BT  
A Fir, 24" dia., bears West, 17 lks., mkd: ¼ S BT

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13195-6)

-----  
Point for the ¼ sec. cor. of secs. 10 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked:

¼  
S 10 | S 11  
T31S | R8W  
1961

from which

A W.Fir, 8" dia., bears S.17½°E., 23 lks., mkd: ¼ S11 BT.  
A fir, 6" dia., bears N.87°W., 31 lks., mkd: ¼ S10 BT.