

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8130)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground for 1/4 Sec. cor. mkd. 1/4 S on the W face, from which
 A cedar, 54" dia., bears S.55°E., 11 lks., mkd: 1/4 S BT.
 A fir, 10" dia., bears S.60°W., 13 lks., mkd: 1/4 S BT.

Reported as not found, 12/1966 - C.S. 54/36-21, DCSO

Troy Rambo -For: Seneca Jones Timber - 1/2002 - M139-47 -

Set - 5/8"x36" rebar with a 2 1/2" alum. cap.
Scribed- 1/4 S3 BT ON A 12" DF - bears N.33°W. 28.5 FT.
 1/4 S2 BT ON AN 11" DF - bears N.44°E. 7.1 FT.
 1/4 S2 BT ON A 9" DF - bears S.84°E. 23.0 FT.
 1/4 S3 BT ON A 7" DF - bears S.25°W. 15.9 FT.
Note - All new BTs were measured to a 6" spike at side center base unless otherwise noted. Bearings were measured with a hand compass with a decl. of 20°E.