

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T32-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8098)

Set a Laurel post 3 ft. long, 3" sq., 20" in the ground for the ¼ sec. cor., and from which

A Fir 12" dia., bears S.2°E., 63 lks. dist. mkd. ¼ s BT.

A Live Oak 6" dia., bears N.18°W., 40 lks. dist. mkd. ¼ S BT.

BLM Resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors, under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16185)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 8 W

¼ $\frac{S\ 35}{S\ 2}$

T 32 S

1977

from which

A Fir 4" dia., bears N.18¼°W., 17½ lks. dist. mkd. ¼S35 BT

A Fir 18" dia., bears S.6¼°W., 52 lks. dist. mkd. ¼ S2 BT.

Ron Quimby - J. Leonard & N. Fromdahl Crew - 9/2013 - C.S. File 65/80-12

Found - 1977 BLM brass cap

18" fir S.6°W., 34.3 (M83-26 N.6°E.) re-tag.

Set - Alum. post 2' east & 2' west.

Note - Area burnt 7/2013

Compass decl. 15½°E.

BLM resurvey by Brandon G Courtright, Cadastral Surveyor, under Group No. 2754, surveyed May/July 2014 - (DCSO records, Vol. 58 page(s) 23380-1)

The ¼ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass (properly) cap mkd. from which the remains of the bearing trees mkd. by Jelley and Carlson in 1976-77

A charred fir stump, 38" dia., bears S.6¼°W., 34.3 ft., no marks visible.

A charred fir snag, 9" dia., bears N.18¼°W., 11.6 ft., with a healed blaze.

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T32-8

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

and new reference monuments

An iron rod, 5/8" dia., 30" long, driven 27" in the ground for a reference monument, bears N.84°12'11"E., 61.31 ft., with alum. cap mkd. RM T31S R8W S35 61.3 FT TO COR 2014, and an arrow pointing to the cor.

An iron rod, 5/8" dia., 30" long, driven 27" in the ground for a reference monument, bears S. 23°05'07"W., 24.79 ft., with alum. cap mkd. RM T32S R8W S2 24.8 FT TO COR 2014, and an arrow pointing to the cor