

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8122)

-----  
Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on the N side for the ¼ sec. cor. from which  
A fir, 9" dia., bears N.10°E., 19 lks., mkd: ¼ S BT.  
A fir, 40" dia., bears S.50°E., 62 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 6/30/1969 - C.S. File 54/36-25

-----  
Also line from sec. cor. (26, 27, 34, & 35)  
1 large BT. Possible to find. Will run in again from 25, 26, 35, & 36 if found.  
Reported as not found.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16198)

-----  
Point for the ¼ sec. cor. of secs. 26 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

T31S R8W  
¼  $\frac{S\ 26}{S\ 35}$   
1977

from which

A fir, 6" dia., bears N.23¾°E., 108 lks., mkd: ¼ S26 BT.  
A fir, 18" dia., bears S.67½°E., 56½ lks., mkd: ¼ S35 BT.  
Corner is located at bottom of descent, slopes N.