

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8124)

Set a stone 16x10x8", 8" in the ground, for 1/4 sec. cor., marked 1/4 on N face, from which

A fir, 16" dia., bears N.45°E., 43 lks., mkd: 1/4 S BT.

A fir, 12" dia., bears S.40°E., 36 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell - 6/17/1969 - C.S. File 54/36-38

This cor. had 2 good firs: approx 12 chains from creek; good line from sec. cor. to the east. Found no blazes or BTs found 2 x's on ridge top but does not line up with anything. Also not to old. Reported as not found.

BLM Dependent resurvey by James E. Jelley, James J. Carlson, Cadastral Surveyors under Group #899 surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16200)

The 1/4 sec. cor, of secs. 23 & 26. determined at record bearing & distance from an original BT:

A fir, 29" dia., bears N.45°E., 43 lks., with fragmentary scribe marks visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.

T31S R5W
1/4 S 23
S 26
1977

from which new BTs

A fir, 23" dia., bears N.38 1/2°W., 49 1/2 lks., mkd. 1/4 S23 BT.

A fir, 5" dia., bears S.72 1/4°E., 14 1/2 lks., mkd. 1/4 S26 BT.

Greg Lang - Aug. 18, 2004 - C.S. File 65/52-4

Found - Brass Cap set by BLM

A 36" Fir bears N.44 3/4°E., 28.80 feet (original)

An 8" Fir bears S.78 3/4°E., 9.30 feet (1977 BLM)

A 26" Fir bears N.38°W., 32.3 feet (1977 BLM)

New - A 6" Fir bears S.57 1/4°W 8.30 ft. scribed "1/4 S26" "BT"

NOTE - We set spikes in the base of all existing & new BTs for measuring distances to the corner; bearings to the trees were measured with a total station & are based on the 1977 resurvey of the north

line of Section 26)
Corners lies the N'ly side of a ridge & on a NE'ly slope.
