TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8127)

Set a Fir post 3 ft. long, 3" sq. 18" in the ground for ¼ sec. cor. mkd ¼ S on the N face, from which
A fir, 20" dia., bears S.5°W., 9 lks., mkd: ¼ S BT.
A chincapin, 8" dia., bears N.70°W., 10 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-47

Found - Orig. 20" D.Fir S.5°W., 5.9 ft. now stob, with bark scribe ¼ S BT.
Orig. 8" Chinquapin, now 11" N.70°W., 6.6 ft. good face.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1967 T31S R8W ¼ S 11 / S 14
New BTs- 24" W.Fir S.42°W., 28.4 ft. mkd: ¼ S14 CS BT.
12" D.Fir N.21°W., 12.4 ft. mkd: ¼ S11 CS BT.
Note - Corner lies on top spur, course E & W.

Howard Johnstone - For: Roseburg Lbr - Nov. 22, 1977 - M65-49

Set - 5/8"x48" iron rod & alum. cap.
6" Fir, N.48½°E., 22.8 ft.
12" Fir, N.21°W., 12.4 ft.
11" Chinquapin, N.70°W., 6.6 ft. Orig. BT.