

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8128-9)

Set a fir post 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on N face, from which

A W.Fir, 18" dia., bears N.2°W., 31 lks., mkd: 1/4 S BT.

A fir, 14" dia., bears S.8°E., 15 lks., mkd: 1/4 S BT.

Reported as not found, 12/1966 - C.S. 54/36-21, DCSO

BLM Dependent resurvey by Dale T. Bedell, Cadastral Surveyors under Group #1338, surveyed Aug/Nov 1986 - (DCSO records Vol 48 Page(s) 18373)

Point for 1/4 sec. cor. of secs. 2 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap marked:

T31S R8W

1/4 S 2
 S 11

1986

from which

A fir, 10" dia., bears S.2°E., 18 lks., mkd: 1/4 S11 BT.

A fir, 6" dia., bears N.27°W., 23 1/2 lks., mkd: 1/4 S2 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Troy Rambo - For: Seneca Jones Timber - 1/2002 - M139-47---

Found - A 14" GF with a healed face - bears S.2°E. 18 lks.

The record 6" DF bearing N.27°W. 23 1/2 lks. - down

Scribed- 1/4 S2 BT ON AN 11" GF - bears N.64°W. 27.4 FT ..

- 1/4 S2 BT ON A 6" GF - bears N.27°E., 28.1 FT .

- 1/4 S11 BT ON A 7" DF - bears S.66°E. 11.0 FT .

Note - All new BTs were measured to a 6" spike at side center base unless otherwise noted. Bearings were measured with a hand compass with a decl. of 20°E.

Fd. Ok by T. Hostetter, 11/2011 - C.S. File 65/75-1