

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8109-10)

Set a laurel post, 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on W side; from which
A pine, 20" dia., bears S.70°E., 18 lks., mkd: 1/4 S BT.
A fir, 20" dia., bears S.75°W., 8 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - 1/21/1974 - C.S. File 56/43-7
----- "S"
R
Found - 28" D.Fir with initials . Chopped into north side of tree, We open & find no evidence of scribing.
40" Sugar Pine with initials "BT" chopped into north face, no scar visible, chopped initials not old.
A point can be located which causes both orig. bearings and distances to fit reasonably well. Also stationing on compass line from N Sec. cor. indicates distance of 2640± to location, no trace of bark scribe on either tree. S.77°W., 5.3 ft. to fir (orig. S.75°W., 5.3 ft.) S.73°E. 12.2 ft to pine (orig. S.70°E., 11.9 ft.) Call to ravine to north misses by about 100 ft. I do not monument.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page)(s) 16186-7)

The 1/4 sec. cor. of secs. 35 & 36 determined at the record bearing & distance from each of the orig. BTs:
A cedar, 40" dia., bears S.70°E., 18 lks. no marks visible. (Rec. Pine)
A fir, 26" dia., bears S.75°W., 8 lks., no marks visible on chopped open blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked: T31S R8W
1/4
S 35 | S 36
1977
from which new BTs
A fir, 33" dia., bears S.50 3/4°E., 22 lks., mkd: 1/4 S36 BT.
A fir, 26" dia., bears S.88 1/2°W., 14 lks., mkd: 1/4 S35 BT.