

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8110)

Set a laurel post, 4 ft. long, 4" sq., 20" in the ground for cor. to secs. 25, 26, 35, & 36, marked T31S R8W S25 on NE face, S36 on SE face, S35 on SW face, S26 on NW face; also 1 notch on S & 1 notch on E angles of same, from which

A fir, 30" dia., bears N.46°E., 25 lks., mkd: T31S R8W S25 BT.

A laurel, 5" dia., bears S.55°E., 22 lks., mkd: T31S R8W S36 BT.

A laurel, 5" dia., bears S.84°W., 12 lks., mkd: T31S R8W S35 BT.

A laurel, 14" dia., bears N.5°W., 51 lks., mkd: T31S R8W S26 BT.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page) (s) 16187)

Point for the cor. of secs. 25, 26, 35, & 36, at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T31S	R8W
<u>S 26</u>	<u>S 25</u>
<u>S 35</u>	<u>S 36</u>
1977	

from which

A madrone, 15" dia., bears N.5½°E., 32 lks., mkd: T31S R8W S25 BT.

A fir, 18" dia., bears S.80½°E., 21½ lks., mkd: T31S R8W S36 BT.

A fir, 16" dia., bears S.6½°W., 114 lks., mkd: T31S R8W S35 BT.

A fir, 14" dia., bears N.54¾°W., 74½ lks., mkd: T31S R8W S26 BT.