

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8111-2)

Set a stone 15x12x10", 8" in the ground mkd. 1/4 on W side for the 1/4 sec. cor. and from which

A Dogwood, 8" dia., bears N.50°E., 32 lks., mkd: 1/4 S BT.

A Dogwood, 6" dia., bears N.65°W., 35 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page) (s) 16189-90)

The 1/4 sec. cor. of secs. 25 & 26, monumented with the orig. basalt stone, 15x12x10", firmly set 10" in the ground, mkd: 1/4 on W face.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T31S R8W

1/4

S 26 | S 25

1977

from which

A fir, 16" dia., bears N.19 1/2°E., 61 lks., mkd: 1/4 S25 BT.

A fir, 16" dia., bears N.46°W., 57 1/2 lks., mkd: 1/4 S26 BT.

Deposit corner stone alongside iron post.