

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8114)

-----  
Set a fir post 3 ft. long, 3" sq., 18" in the ground & marked 1/4 S on the W side for the 1/4 sec. cor., from which  
A Pine, 20" dia., bears S.27°E., 26 lks., mkd: 1/4 S BT.  
A Chincapin, 10" dia., bears N.66°W., 84 lks. mkd: 1/4 S BT.

Douglas Co. Surveyors Office - John Powell - 6/19/1969 - C.S. File 54/36-26

-----  
Reported as not found.  
No trace of anything. Probable old burn. BTs 20" Pine, Chinquapin.

BLM Resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors, under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16192)

-----  
Point for the 1/4 sec. cor. of secs. 23 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 24" in the ground with brass cap marked:

T 31 S R 8 W  
1/4  
S 23 | S 24  
1977

from which

A Fir, 6" dia., bears N.77 1/2°E., 14 1/2 lks., mkd: 1/4 S24 BT.  
A Fir, 6" dia., bears N.89°W., 8 lks., mkd: 1/4 S23 BT.

Mark Smalley - For: Roseburg Resources - 7/2002 - C.S. File 65/44-12

-----  
Found - 1977 BLM IPBC  
7" Fir N.77 1/2°E., 14.5 lks. (9.6') Good, healed face.  
11" Fir N.89°W., 8.0 lks., (5.3') Good, healed face.  
New - 2002 - 10" Fir S.71°E., 17.2' scribed "1/4 S BT"  
2002 - 7" Fir N.18°W., 28.8' scribed "1/4 S BT"