

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8114)

Set a stone 14x12x12", 8" in the ground, marked with 3 notches on the S & 1 notch on the E. angle of same for cor. of secs. 13, 14, 23, & 24, from which

A Live Oak, 4" dia., bears N.46°E., 10 lks., mkd: T31S R8W S13 BT.

A Live Oak, 10" dia., bears S.15°E., 44 lks., mkd: T31S R8W S24 BT.

A Live Oak, 4" dia., bears S.80°W., 20 lks., mkd: T31S R8W S23 BT.

A Laurel, 8" dia., bears N.45°W., 36 lks., mkd: T31S R8W S14 BT.

Douglas Co. Surveyors Office - John M. Powell - 6/12/1969 - C.S. File 54/36-26

Fd intersection of N-S E-S lines. Good dist. of 9.50 chains from summit. No trace of cor. BTs 3 live oak 1 laurel.
Reported as not fd.

Dennis A. Crowe, US Plywood Corp. - Jan. 1973 - M47-60 & C.S. File 55/279

Found - A diligent search was made yielding no acceptable evidence of adequate corner monumented.

Set - 36" Alum. cap, iron pipe, 24" into the ground.
18" Fir, scribed on the wood bearing S.3°E., 28.5 ft
11" Madrone scribed on the wood bearing S.57°W. 2 ft
13" Fir, scribed on the wood bearing N.35°W., 10 ft.
9" Madrone scribed on wood bearing N.27½°E., 10.5 ft

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16192-3)

Point for the cor. of secs. 13, 14, 23, & 24, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground, with brass cap marked:

T31S R8W
S 14 | S 13
S 23 | S 24
1977

from which

A fir, 17" dia., bears N.18¼°E., 36 lks., mkd: T31S R8W S13 BT.

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 8" dia. bears S.49°W., 45 lks. mkd: T31S R8W S23 BT
A fir, 18" dia., bears N.50½°W., 15½ lks., mkd. T31S R8W
S14 BT.

No suitable tree available within limits in sec. 26.
From this point, a cor. established by Dennis Crowe, in 1972,
bears S.32°02'E., 0.20 chs., monumented with an iron post,
1½" dia., firmly set, projecting 8" above ground, with
aluminum cap mkd.

	T31S	R8W
LS	S	C
8	S 14	S 13
4	S 23	S 24
5	1972	

from which bearing trees mkd. by Crowe
A madrone, 10" dia., bears N.27½°E., 15½ lks., with
fragmentary scribe mks visible on partially open blaze.
A fir, 19" dia., bears S.3°E., 43½ lks., with healed
blaze.
A madrone, 12" dia., bears S.48½°W., 3 lks., with
fragmentary scribe marks visible on open blaze.
A fir, 15" dia., bears N.35°W., 15 lks., with healed
blaze.

Mark Smalley - For: Roseburg Resources - 5/30/2001 - C.S.
File 65/37-19

Found - 1977 BLM Brass cap on iron pipe, properly marked.
18" Fir now 24" N.50°W., 10.5' healed.
7" Fir now 13" S.53°W., 30.3' healed. (M65-49)
Alum. cap S.29¾°E., 13.2' (M65-49)
18" Fir N.20°E., 23.0' snag. (M65-49)
New BTs- 20" Fir S.18°E., 3.6' scribed "S 24 BT"
21" Fir S.86°W., 14.1' scribed "S 23 BT"