

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8116)  
-----  
Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on the W side for the ¼ sec. cor. from which  
A fir, 18" dia., bears E. 26 lks., mkd: ¼ S BT  
A fir, 12" dia., bears N.30°W., 12 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-43  
-----  
Found - Un-recorded ¾"X18" iron pipe at corner.  
Orig. 18" D.Fir now down, East 17.2 ft. faint bark scribe ¼ BT  
No evidence of NW BT.  
Set brass cap at ¼ cor. mkd: COUNTY SURVEYORS T31S R8W  
OFFICE 1967 ¼ S14|S13  
New BTs- 9" Cedar N.36°W., 15.2 ft. mkd: ¼ S14 CS BT.  
6" D.Fir N.50°E., 9.5 ft. mkd: ¼ S13 CS BT.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16196)  
-----  
The ¼ sec. cor, of secs. 13 & 14, perpetuated and recorded by Byron, County Surveyor, in 1967, monumented with an iron post, 1¼" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd.  
from which the remains of an original bearing tree  
A root hole, bears East, 26 lks., with a down fir alongside, 20" dia., with fragmentary scribe marks visible on bark blaze.  
and the remains of bearing trees mkd. by Byron  
A root hole, bears N.50°E., 14½ lks., with a down fir alongside, 8" dia., with fragmentary scribe marks visible on open blaze.  
A root hole, bears N.36°W., 23 lks., with a down cedar alongside, 6" dia., with fragmentary scribe marks visible on open blaze.  
and new bearing trees  
A fir, 9" dia., bears N.41°E., 30½ lks., mkd. ¼ S13 BT.  
A fir, 4" dia., bears S.14°W., 41½ lks., mkd. X BT.

Fd. BC & 4 BTs by H Johnstone - Nov. 1977 - M65-49

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dan Saily, Lone Rock - Crew: Brett Ragon, Alfredo Martinez,  
Trevor Clemo & Zachary Holland - 12/2025 - M186-53

-----

Found - 2" brass cap and iron pipe marked county surveyors  
office T31S R8W ¼ SS14 S13 1967, per CS 54/36-43.  
27" D. Fir bears N.46°E. 19.5 ft. M65-49 (Rec. N.48°E.  
20.4 ft.) with a healed face and BLM tag.

New - ¾" iron pipe at ground level along side county pipe.  
17" D. Fir bears N.27¾°W. 29.4 ft. We scribe ¼ S14 BT  
and tag.

9" D. Fir bears S.55°W. 14.5 ft. We scribe ¼ S14 BT  
and tag.

17" D. Fir bears S.34¾°E. 29.1 ft. We scribe ¼ S13 BT  
and tag.

Notes - All other record bearing trees are down or rotted away.  
The corner monument lies on a North facing slope 450ft. North of  
gravel surface, BLM logging road #31-8-13.0. The top of the  
monument lies 0.8 ft. above ground level. We place a 5½ ft. tall  
galvanized, steel U-post 1.0 ft. North. NAD 83 (2011) latitude  
N.42°52'32.34", longitude W.123°36'13.16"