

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8118)

-----  
Set a fir post 3 ft. long, 3" sq. 18" in the ground, marked ¼ S on the W face, for the ¼ sec. cor. from which  
A laurel, 12" dia., bears N.75°E., 8 lks., mkd: ¼ S BT.  
A laurel, 12" dia., bears N.30°W., 25 lks., mkd: ¼ S BT.

Reported as not found DCSO Dec. 1966 - C.S. file 54/36-21

BLM Dependent resurvey by Dale T. Bedell, Cadastral Surveyors under Group #1338, surveyed Aug/Nov 1986 - (DCSO records Vol 48 Page(s) 18371)

-----  
Point for the ¼ sec. cor. of secs. 11 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd.

T31S R8W  
¼  
S 11|S 12  
1986

from which

A fir, 9" dia., bears S.51°W., 54 lks., mkd. ¼ S11 BT.  
A fir, 8" dia., bears N.30°W., 68½ lks., mkd. X BT.

No suitable trees available in sec. 12.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

David Edwards - For: Seneca Jones Timber & Roseburg Resources - Nov. 2017 - M173-76

-----  
Found - 1986 BLM BC  
A 12" dia., fir bears S.51°W., 35.6'  
A 12" dia., fir bears N.30°W., 45.2'  
Both with healed blaze.  
Set - A 6 ft. steel post 2 ft North.