

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8118)

-----  
Set a cedar post 4 ft. long, 4" sq., 20" in the ground for the corner to Secs. 1, 2, 11, & 12, marked T31S R8W S1 on the NE face, S12 on the SE face, S11 on the SW face and S2 on the NW face. Also 5 notches on the S and 1 notch on E angles of same, from which

A laurel, 12" dia., bears N.50°E., 22 lks., mkd: T31S R8W S1 BT.

A fir, 24" dia. bears S.40°E., 6 lks. mkd: T31S R8W S12 BT

A laurel, 15" dia., bears S.25°W., 26 lks., mkd: T31S R8W S11 BT.

A fir, 15" dia. bears N.30°W., 46 lks. mkd: T31S R8W S2 BT

-----  
Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Cliff stone - Jan. 1967 - C.S. File 54/36-49

-----  
Found - Orig. 15", now 29" D.Fir, N.30°W. 30.2 ft., faint bark scribe. T31S R8W S

Orig. 24", now 44" D.Fir, S.40°E. 4.0 ft., faint bark scribe. "T31" "W"

Orig. 15", now 22" Laurel, S.25°W. 17.2 ft. rotten center.

(All distances to approx. face)

Set brass cap at cor. mkd: COUNTY SURVEYORS T31S R8W  
OFFICE S 2 | S 1  
1967 S 11 | S 12

New BTs- 15" Cedar S.51°W., 12.5 ft. mkd: T31S R8W S11 CS BT.

14" Cedar N.29°W., 16.7 ft. mkd: T31S R8W S2 CS BT.

15" D.Fir N.30°E., 47.0 ft. mkd: T31S R8W S1 CS BT.

-----  
BLM Dependent resurvey by Dale T. Bedell, Cadastral Surveyors under Group #1338, surveyed Aug/Nov 1986 - (DCSO records Vol 48 Page(s) 18372)

-----  
The cor. of secs. 1, 2, 11, & 12, perpetuated & recorded by Powell, in 1967, monumented with an iron post, 1½" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir stump, 42" dia., bears S.50°E., 7 lks., with illegible scribe marks visible on bark. (Record, S.40°E., 6 lks.)

A madrone snag, 25" dia., bears S.25°W., 27 lks., no visible marks.

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 30" dia., bears N.30°W., 48 lks. dia., with illegible scribe marks visible on bark. (Rec 45 lks.) and the remains of bearing trees mks. by Powell

A fir stump, 18" dia., bears N.30°E., 72 lks., with illegible scribe marks visible on rotted blaze.

A cedar, 20" dia., bears S.51°W., 19 lks., with scribe marks T31S R8W CS visible on partially healed blaze.

A cedar, 17" dia., bears N.29°W., 26 lks., with scribe marks T31S R8W 32 CS visible on partially healed blaze. and new bearing trees

A fir, 18" dia. bears N.27°E., 105 lks. mkd T31S R8W S1 BT

A fir, 6" dia., bears S.20°E., 26 lks. mkd T31S R8W S12 BT (Latitude 42°53'52.63N - Longitude 123°36'08.59"W NAD 1927)

From this point, NGS triangulation station "Live Oak" bears N.17°59'30"W., 232.806 chs., monumented with a bronze tablet, set in a concrete post, 10" sq., firmly set flush with the surface of the ground, marked LIVE OAK 1942.

Ron Quimby - For: Roseburg Resources - Oct. 2017 - M173-67

Found - Brass cap per 1967 renewal.

Original BTs burned in fire

Set 5/8"x30" iron rods with metal fence posts as follows:

Bears S.59°W., 10.0'

Bears S.17°E., 13.0'

Bears N.67°E., 12.0'

Bears N.59°W., 14.0'

FD. as per rec. by D Edwards - Nov. 2017 - M173-76