

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7312)

Set a Fir post 4 ft. long, 4" sq., 20" in the ground for the cor. to secs. 1, 2, 35 and 36, mkd. T30S R8W S36 on the NE. face; T31S S1 on the SE. face; S2 on the SW. face; and S35 on the NW. face. Also 1 notch on the E. and 5 notches on the W. angles of same, from which

 A Pine 24" dia. bears N.60°E., 168 lks mkd T30S R8W S36 BT
 A Pine 7" dia., bears S.28°E., 50 lks. mkd. T31S R8W S1 BT
 A Pine 10" dia., bears S.58°W., 102 lks mkd T31S R8W S2 BT
 A Pine 30" dia., bears N.10°W., 35 lks mkd T30S R8W S35 BT

Arthur Evans - For: Martin Bros. Box Co. - April 1956 - C.S. File 42/197-1

Point for the corner established by proportionate measurement, between ¼ corners.

Set a 3" x 3" x 36" D.Fir stake. Blaze and scribed BTs:

 10" madrone S.78½°E., 13.2 ft. mkd. T31 R8 S1 R.E. 1741 BT
 3" D.Fir S.72°W., 6.2 ft. mkd. X BT.
 8" madrone N.51°E., 17.9 ft. mkd. T30 R8W S36 RE 1741 BT.
 7" madrone N.6°W., 17.2 ft. mkd. T30 R8 S35 RE 1741 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 25, 1967 - C.S. File 54/36-75

Found - Wood post at corner.

 3" now 6" D.Fir N.82°W., 6.2 ft., shows scar. (rec. N.72°W.)
 7" now 8" Laurel N.6°W., 17.0 ft., bark scribed, T30S R8W S35 BT
 10" now 12" Laurel S.78½°E., 13.2 ft., bark scribed, T31S R8W S1 RE 2741
 8" now 9" Laurel N.51°E., 17.9 ft., bark scribed, T30S R8W S36 BT

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 8 W
S 35 | S 36

S 2 | S 1
1967

New BT - 5" D.Fir S.14½°W., 19.8 ft. mkd. S2 CS BT.
Reblazed and rescribed:

 8" Laurel N.6°W., 17.2 ft. mkd. T30S R8W S35 CS BT
 12" Laurel S.78½°E., 13.2 ft. mkd. T31S R8W S1 CS BT
 9" Laurel N.51°E., 17.9 ft. mkd. T30S R8W S36 CS BT.

(Cont. Next Page)

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T30-8

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Douglas Co. Surveyors Office - John M. Powell, and crew -
March 31, 1971 - C.S. File 53/67-8

Found - 5" now 5" D.Fir S.14½°W., 19.8 ft., pitched over
scribe.
8" now 8" Laurel N.6°W., 17.2 ft., scribe visible.
12" now 12" Laurel S.78½°E., 13.2 ft., scribe
visible.
9" now 9" Laurel N.51°E., 17.9 ft., scribe visible.
Also found brass cap, out of ground.
RESET brass cap at cor. mkd. as in 1967.
New BTs- 7" D.Fir S.83½°E., 23.4 ft. scribed T31S R8W S1 CSBT
6" D.Fir N.19°E., 17.0 ft. scribed T30S R8W S36 CSBT

Fd.OK, Dec. 1981 by H. Johnstone - M 89-79
Fd. OK, Jan. 2002 by T. Rambo - M139-47

Ron Quimby - For: Roseburg Resources - Oct. 2017 - M173-67

Found - Brass cap per 1971 renewal.
5" now 18" D.Fir bears S.14°30'W, 19.8' fully healed
scribe.
8" now 12" laurel bears N.6°W., 17.2' burned out
scribe.
12" now 18" laurel bears S.78°30'E., 13.2' fully
healed scribe.
9" now 12" laurel bears N.51°E., 17.9' fully healed
scribe.
7" now 16" D.Fir bears S.83°30'E., 23.4' fully
healed scribe.
6" now 17" D.Fir bears N.19°E., 17.0' fully healed
scribe.