

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 1, T32-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8097)

Set a Fir post 3 ft. long, 3" sq., 18" in the ground mkd. ¼ S on the N. side for the ¼ sec. cor., from which
A Laurel 6" dia., bears S.62°E., 33 lks. mkd. ¼ S BT.
A Laurel 6" dia., bears N.30°W., 38 lks. dist. mkd. ¼ S BT

BLM Resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors, under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16183)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 8 W
¼ $\frac{S\ 36}{S\ 1}$
T 32 S
1977

from which

A Fir 6" dia., bears N.69½°E., 37½ lks. mkd. ¼ S36 BT.
A Fir 8" dia., bears S.17½°W., 59 lks. mkd. ¼ S1 BT

BLM resurvey by Brandon G Courtright, Cadastral Surveyors, under Group No. 2754, surveyed May/July 2014 - (DCSO records, Vol. 58 page(s) 23367-8)

The ¼ sec. cor. of secs. 1 & 36, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.

from which the BTs mkd. by Jelley and Carlson in 1976-77

A fir, 12" dia., bears N.69½°E., 24.8 ft., with a healed blaze.

A fir, 11" dia., bears S.17°E., 38.4 ft., with a healed double blaze. (Record, S.17½°W., 38.9 ft.)

and a bearing tree mkd. by person(s) unknown

A fir, 17" dia., bears S.28½°E., 41.0 ft., with a healed blaze and with a Roseburg Timber Products locator tag.